

MonoLight LED

- Only one battery needed
- Automatic solar switch
- 180 mm dia polycarbonate lens
- Robust locking of battery compartment
- Continuous/ flashing mode
- High quality LEDs with nearly unlimited life time
- BS 3143 pt 2 and EN 12352 compliant



 Light source LED	 Light colour red, amber, blue	 Eff. light intensity 15 cd	 Flash rate 60-70 fl./min.
 Weight 0.5 kg	 Dimensions (LxWxH) 185 x 120 x 340 without bracket	 Operating voltage 6V	

MonoLight LED

Ref. No.

Amber MonoLight c/w attached plastic cone bracket	111 602-60
Red MonoLight c/w attached plastic cone bracket	111 602-63

Accessories and Spare parts

Ref. No.

NiKo key	070 090-1
NiKo bracket for mounting the MonoLight on barriers	365 519
Bracket for mounting the MonoLight / SignLite on traffic cones	292 032-3
Dry Cell Battery Premium 800, 6V, 7 Ah – 9 Ah	155 051
Battery Konstant 25, 6V, 25-28 Ah	155 054



Red MonoLight



Battery change



NiKo-Key

Operating time with one battery set

With battery Premium 800	steady light 300 hrs / flashing light 1200 hrs
With battery Konstant 25	steady light 950 hrs/ flashing light 3800 hrs



More information
NIS-02042
To be entered on nissen-germany.com