

VarioSign-Red X Toblerone System

- VMS system is equipped with VarioSign 5x4k-420 with Red/white LEDs and a Prism board
- Depending on the selected arrow position on VMS, the 610 arrow displays a corresponding arrow left or right and when top VMS board displays Red X, the prism displays "CONVOY VEHICLE NO OVERTAKING"
- Ideal for impact protection vehicles offering advanced superior warning and information to oncoming motorists
- System can be programmed with "wicket" signs for lane closure information.
- According to EN12966 and TOPAS approved and DfT authorised



Dimensions (WxH)
2100 x 1680 mm (screen)



Material housing
aluminium, seawater resistant



Light colour
red, white



LED pitch
20 mm



Operating voltage
12 / 24V

VarioSign-Red X Toblerone System

Ref. No.

Nissen VarioSign 5k x 4k - 420 with Red/White LEDs	229 291-54-113
Nissen VarioSign 5k x 4k - 420 with Red/White LEDs - part populated:	229 291-54-123

Accessories and Spare parts

Ref. No.

Standard cable remote control	129266-26-02
Memory stick 8 MB	320227-8
Prism Sign NUK, external dimensions 1856 x 1745 mm, arrow left, arrow right, CONVOY VEHICLE NO OVERTAKING	081628-21



Hard-shoulder use 2-fold



Live lane use - arrow left



Live lane use - arrow right



Standard cable remote



More information
NIS-02034
To be entered on nissen-germany.com