



Products Details

**Twofold Warning System
Multi-Light 340 LED Flash L9M**

tested according to German Standards and EN 12352

- Lamp class L9M according to EN 12352
- Each lamp with four Super-LED
- Lens diameter 340 mm
- Automatic day/night adaptation, switchable to solar switch
- Consisting of one master lamp and one slave lamp, cable length between the lamps 6 m
- Master lamp with 5 m connecting cable with battery clips
- Further multiple systems on request
- Examples of application (depending on country-specific regulations)
 - on service and maintenance vehicles
 - on gritting vehicles
 - on building site vehicles
 - on pre-warning trailers
 - on warning trailers



Twof. W. S. Multi-Light 340 LED Flash L9M



Twofold Warning S. with bracket



Box for rechargeable batteries

Twofold Warning System
Multi-Light 340 LED Flash L9M

Ref. No.

Twofold Warning Light System Multi-Light 340 LED Flash L9M Type
690/1F NiBus
12/24 V, 5 m connecting cable with battery clips

122 312-201

Accessories and Spare parts

Ref. No.

Box for rechargeable batteries 12 V up to 230 Ah, lockable

190 230-1

Operating time with one set of batteries

With rechargeable battery 12 V, 180 Ah

1500 hrs

With rechargeable battery 12 V, 100 Ah

750 hrs

Technical data

Light colour

yellow

Eff. light intensity day

4900 cd

Eff. light intensity night

625 cd

Aver. power consumption day at 12 V

0,1 A

Aver. power consumption night at 12 V

0,07 A

Blink-/flash rate

60 fl./Min.