



## Products Details

### Twofold Warning System "Zyklop 220" Multi-Light 220 LED Flash L8M

tested according to EN 12352

- Lamp class L8M-03 according to EN 12352
- Each lamp only one Super-LED
- Lens diameter 220 mm
- Automatic day/night adaptation
- 5 m connecting cable with battery clips
- Consisting of 1 master lamp and 1 slave lamp, cable length between the lamps ca. 3 m
- Further multiple systems on request
- Examples of application (depending on country-specific regulations)
  - for advance warning in front of building sites
  - for advance warning in front of danger spots
  - on service and maintenance vehicles

Twofold Warning System  
"Zyklop 220" Multi-Light 220 LED Flash L8M

Ref. No.

Twofold Warning Light System "Zyklop 220" Multi-Light 220 LED Flash L8M type 671/F NiBus, 12/24 V, with 5 m connecting cable with battery clips

122 222-201

#### Accessories and Spare parts

Ref. No.

Box for rechargeable batteries 12 V up to 230 Ah, lockable

190 230-1

Bracket for tubes up to 82 mm

365 522-12

#### Operating time with one set of batteries

With rechargeable battery 12 V, 100 Ah

1500 hrs

#### Technical data

Light colour	yellow
Eff. light intensity	500 cd
Aver. power consumption day at 12 V	0,06 A
Aver. power consumption night at 12 V	0,05 A
Blink-/flash rate	60 fl./min.
Operating voltage	12/24 V

