

Twofold Warning System Zyklop 220

- Energy-efficient design with only one LED
- Automatic day/night adaptation, switchable to solar switch
- 5 m connecting cable with battery clips
- Consisting of one master lamp and one slave lamp, cable length between the lamps ca. 3 m



Light colour
yellow



Eff. light intensity
1500 cd



Av. power consumpt. day
0,28 A



Operating voltage
12/24V



Blink-/flash rate
60 fl./min.



Light source
1 LED



Weight
1,2 kg/set

Twofold Warning System Zyklop 220

Ref. No.

Twofold Warning Light System Zyklop 220 Multi-Light 220 LED L8H
Type 671/1 NiBus, 12/24V,
with 5 m connecting cable with battery clips

122 222-1

Accessories and Spare parts

Ref. No.

Box for rechargeable batteries 12 V up to 230 Ah, lockable
Bracket for tubes up to 82 mm

190 230-11

365 522-12

Operating time with one battery set

With rechargeable battery 12 V, 100 Ah	440 hrs
With rechargeable battery 12 V, 180 Ah	800 hrs
With rechargeable battery 12 V, 230 Ah	1000 hrs



Twofold Warning System Zyklop 220



Twofold Warning System with bracket



Box for rechargeable batteries



More information
NIS-01411
To be entered on nissen-germany.com

Test number
V3-24-2013