

Synchros

- Ideal system for incident management
- Early recognition of danger spots
- Synchronized light sequence to ensure safe passing of the hazardous spot
- Space-saving placement in compact storage & charging box
- Firm road grip when studs are placed on the road
- Easy and quick deployment for instant lane closure
- Two Synchros can be combined with each other
- Charging cable with 2-pole car plug
- Approved for use by UK DfT



	Light colour yellow or blue		Aperture angle horizontal / vertical 15°		Operating voltage 10 - 30 V DC		Av. power consumption with completely discharged battery 0,5 A
	Operation time ca. 16 hrs		Dimensions LED guide light element 100 x 90 x 25 mm		Dimensions (LxWxH) transport and storage case 260 x 160 x 125 mm		Weight 2.5 kg

Synchros

	Ref. No.
Amber Synchros studs	141 060-1
Blue Synchros studs	141 060-2

Accessories and Spare parts

	Ref. No.
Amber stud for Synchros	241 060-1
Blue stud for Synchros	241 060-2
Mains charger, UK version (not illustrated)	070 157-2
Charging cable for Synchros with straight plug	400 225-2
Bracket for mounting stud over a traffic cone	392 337-11



Synchros stud



Blue version



Charging cable



More information
NIS-02038
To be entered on nissen-germany.com